

(12) AUSTRALIAN PATENT ABSTRACT

(19) AU

(11) AU-A-28074/84

(54) UNIVERSAL KEYBOARD MOUNT AND ADJUSTABLE KEYBOARD SUPPORT
(71) KNOLL INTERNATIONAL, INC.
(21) 28074/84 (22) 16.5.84 (24) 16.5.83
(31) 494809 (32) 16.5.83 (33) US
494810 16.5.83 US
(43) 22.11.84
(51)³ B41J 5/08
(72) BRUCE R. HANNAH, WILLIAM I. STEPHENS, GEORGE WILMOT, ERIC
J. ARMSTRONG, JAMES B. ELTON, HAROLD A. SMITH AND PHILIP
J. CAMPBELL

(74) SF


(57) Claim

1. A universal keyboard mount comprising a keyboard mounting plate, a carrier for said keyboard mounting plate, said carrier having a cushioning section thereof adapted to cushion one surface of a keyboard, said keyboard mounting plate having a cushioning section thereof adapted to cushion an opposed surface of said keyboard, and means mounting said keyboard mounting plate and said carrier for adjustable positioning of said cushioning sections thereof toward and away from each other, so as to engage firmly said keyboard.

13. An adjustable keyboard support comprising a rear housing for pivotally supporting one end of a parallel link mechanism, a front housing carried by the other end of

28 074 84

28 074/84



(12) PATENT ABRIDGMENT (11) Document No. AU-B-28074/84
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 579819

(54) Title
UNIVERSAL KEYBOARD MOUNT AND ADJUSTABLE KEYBOARD SUPPORT

(51)* International Patent Classification(s)
B41J 005/08 B41J 029/06

(21) Application No. : 28074/84

(22) Application Date : 16.05.84

(30) Priority Data

(31) Number	(32) Date	(33) Country
494809	16.05.83	US UNITED STATES OF AMERICA
494810	16.05.83	US UNITED STATES OF AMERICA

(43) Publication Date : 22.11.84

(44) Publication Date of Accepted Application : 15.12.88

(71) Applicant(s)
KNOLL INTERNATIONAL, INC.

(72) Inventor(s)
BRUCE R. HANNAH; WILLIAM I. STEPHENS; GEORGE WILMOT; ERIC J. ARMSTRONG;
JAMES B. ELDON; HAROLD A. SMITH; PHILIP J. CAMPBELL

(74) Attorney or Agent
SPRUSON & FERGUSON

(57) Claim

1. An adjustable keyboard support comprising:

a base;

a pair of spaced generally parallel co-extensive elongated links,
each link having an end pivotally attached to said base;

a keyboard mounting plate assembly including a plate to receive and
support a keyboard, said plate being pivotally attached to the other ends
of said links so that during movement of said plate, the orientation of
said plate remains substantially unchanged, said plate assembly further
including clamp means to engage said keyboard to retain said keyboard at a
position supported on said plate;

a gas cylinder operatively extending between said base and plate
assembly to effectively apply a force to aid in maintaining a desired
position of said plate.

COMMONWEALTH OF AUSTRALIA
PATENTS ACT 1952COMPLETE SPECIFICATION

(ORIGINAL)

FOR OFFICE USE:

28074/84.

Class Int. Class

Complete Specification Lodged:

Accepted:

Published:

Priority:

Related Art:

SEARCHED
SERIALIZED
INDEXED
FILED
JUN 1984
MELBOURNE
AUSTRALIA

Name of Applicant: KNOLL INTERNATIONAL, INC.

Address of Applicant: 655 Madison Avenue, New York, New York
10021, United States of AmericaActual Inventor(s): BRUCE R. HANNAH, WILLIAM I. STEPHENS,
GEORGE WILMOT, ERIC J. ARMSTRONG, JAMES B.
ELDON, HAROLD A. SMITH and PHILIP J.
CAMPBELLAddress for Service: Spruson & Ferguson, Patent Attorneys,
Level 33 St Martins Tower, 31 Market
Street, Sydney,
New South Wales, 2000, Australia

Complete Specification for the invention entitled:

"UNIVERSAL KEYBOARD MOUNT AND ADJUSTABLE KEYBOARD SUPPORT"

The following statement is a full description of this invention,
including the best method of performing it known to us

ABSTRACT OF THE DISCLOSURE:

A universal keyboard mount is disclosed utilizing a keyboard mounting plate and a carrier for that plate. The carrier has a cushioning section which cushions one surface of the keyboard. The keyboard mounting plate has a cushioning section which cushions an opposed surface of the keyboard. The keyboard mounting plate and carrier are adjustably positioned so that the cushioning sections thereof may move toward and away from each other. Bumpers adjustably mounted are utilized to prevent the keyboard from striking adjacent surfaces of a work surface as the keyboard mount is moved.

An adjustable keyboard support is also disclosed constituted by a rear housing that pivotally supports one end of a parallel link mechanism. A front housing is carried by the other end of the parallel link mechanism, and pivotally supports a keyboard mounting plate. The parallel link mechanism permits upward and downward movement of the keyboard mounting plate without change in the tilt of that plate. A gas cylinder mechanism coupled to the front housing changes the vertical position of the same, and a slide plate adjustment mechanism provides forward and backward movement of the keyboard mounting plate.

~~BACKGROUND AND BRIEF DESCRIPTION OF THE INVENTION:~~

This invention relates to a universal keyboard mount. It has particular application to the mounting of a separable computer keyboard. It also relates to an adjustable keyboard support and is particularly directed to providing an adjustable support for a computer keyboard that may be stored under a work surface and moved from beneath

14 AUG 70

BACKGROUND AND BRIEF DESCRIPTION OF THE INVENTION

This present invention relates to a keyboard mount.

Mounts for positioning a computer keyboard are known. Most involve a simple surface onto which the keyboard is positioned and on which it is free to move without restraint.

Supports for adjustably positioning a separable keyboard are known. One is schematically described in "The New Work-Station" by John Pile in Interiors, November 1982, pages 92, 93. The keyboard support disclosed in that article moves through a range of tilt to suit a user's needs and also moves up and down, independently of tilt angle, to bring the keyboard to a desired position. Mechanical linkages are shown in the schematic illustration in the article, and thus the user is required manually to move the keyboard support to all desired positions (raising and lowering).

It is the object of the present invention to overcome or substantially ameliorate the above disadvantages.

There is disclosed herein a keyboard support comprising:

a base;

a pair of spaced generally parallel co-extensive elongated links, each link having an end pivotally attached to said base;

... a keyboard mounting plate assembly including a plate to receive and support a keyboard, said plate being pivotally attached to the other ends of said links so that during movement of said plate, the orientation of said plate remains substantially unchanged, said plate assembly further including clamp means to engage said keyboard to retain said keyboard at a position supported on said plate;

... a gas cylinder operatively extending between said base and plate assembly to effectively apply a force to aid in maintaining a desired position of said plate.



~~mounting plate is achieved in the present invention.~~

~~The invention will be more completely understood by reference to the following detailed description, taken in conjunction with the appended drawings.~~

BRIEF DESCRIPTION OF THE DRAWINGS:

Fig. 1 is a perspective view, looking downwardly, of a universal keyboard mount and an adjustable keyboard support embodying the present invention.

10 Fig. 2 is an exploded perspective view, looking upwardly, of a part of the keyboard mount and support of Fig. 1.

Fig. 3 is an exploded perspective view showing the details of a parallel link mechanism incorporated in the universal keyboard mount and adjustable keyboard support of Fig. 1.

Fig. 4 is a schematic drawing illustrating the operation of the parallel link mechanism of Fig. 3.

20 Fig. 5 is an exploded perspective view of a part of the universal keyboard mount and adjustable keyboard support of Fig. 1, showing the details of a slide plate mechanism incorporated therein.

Fig. 6 is an exploded perspective view of a portion of the universal keyboard mount and adjustable keyboard support of Fig. 1, showing the details of the gas cylinder actuating the structure.

DETAILED DESCRIPTION:

Referring to Fig. 1, a universal keyboard mount is shown that is constituted by a keyboard mounting plate 10 having a curled end 10a that carries a cushion pad 12 thereon. The cushion pad 12 is adapted to cushion one



surface of a keyboard (not shown). The keyboard mounting plate 10 is carried by a carrier 14 (see also Fig. 2). The carrier 14 includes upstanding posts 16 which mount a carrier cushioning section 18 therebetween. The carrier cushioning section 18 may be formed from a resilient roll 18a mounted about an inner tube 18b. The cushioning member 18 cushions a surface of the keyboard that is opposed to the surface that is cushioned by the cushioning section 12 of the keyboard mounting plate 10.

The keyboard mounting plate 10 and the carrier 14 are held against each other with relative adjustable positioning by means of studs 20 which depend from the underside of the keyboard mounting plate 10. The studs 20 pass through corresponding slots 22 in the carrier 14. Locking knobs 24 which thread onto the ends of the studs 20 are tightened to hold securely the mounting plate 10 against the carrier 14 in any particular position, and are loosened to permit relative movement of the two cushioning sections 12 and 18 toward and away from each other by appropriate movement of the studs 20 in the slots 22.

Bumpers 26 are included which preferably constitute resilient balls, each mounted upon one end of a rod 28 that is bent to define an obtuse angle. The other end of each rod is carried by the tubing 18b that forms a support for the resilient cushioning roll 18a. Each rod 28 is thus moveable along the axis of the tubing 18b, and is also pivotal about that axis, held in position by set screw 28a. Thus the resilient bumpers 26 may be moved toward and away from each other (in a direction generally transverse to that of the movement of the cushioning sections 12 and 18), and

additionally (by virtue of the pivotal movement) in planes generally perpendicular to the direction of movement of the bumpers toward and away from each other. The bumpers accordingly have a freedom of movement along three orthogonal axes, and hence may be positioned as desired to protect various sized keyboards which may be mounted on the mounting plate against damage from impact with adjacent work surfaces as the mounting plate is moved.

As shown in Fig. 1, the keyboard mounting plate 10 and the carrier 14 are coupled to a slide plate 50. The sides of the slide plate 50 include spring-loaded bearing blocks 52 that ride in slide tracks 54 of a track plate 56 that may be mounted to the underside of a work surface. The details of the slide plate 50 and the bearing blocks 52 are shown in Fig. 5. As noted in that figure, the sides of the plate 50 are cut out to accommodate the bearing block 52, and springs 58 provide the spring loading that urge the bearing blocks against the sides of the tracks 54. The bearing

blocks serve as sole bearing members and also as friction members.

The slide plate 50 and track plate 56 thus provide for movement of the keyboard mounting plate 10 forwardly and backwardly with respect to a work surface; friction or drag provided by the bearing blocks serves to semi-permanently position the plate 50 relative to plate 56. Appropriate stops (not shown) may be included, if desired, to prevent the complete removal of the bearing blocks 52 out of the tracks 54.

As noted from Fig. 5, the underside of slide plate 50 includes a stud 60 affixed thereto that passes respectively through an upper bearing 62, a rear housing 64, a lower bearing 66, and a bearing plate 68, finally to be threaded onto nut 70 held by lock washer 72. The bearings 62 and 66 provide for pivotal movement of the rear housing with respect to the slide plate 50 about an axis which is generally perpendicular to that slide plate, for at least about 180° of pivotal movement and preferably for 360° of pivotal movement. The importance of this pivotal movement of the rear housing will be described in more detail below.

Referring to Fig. 2, it will be recalled that the keyboard mounting plate 10 is ultimately supported by assembly 30. That assembly 30 is in turn coupled to a front housing assembly 74, the details of which are shown in Fig. 3. Referring to that figure, the front housing assembly 74 includes, in addition to the support assembly 30, upper and lower bearings 76 and 78 on opposite sides of a front housing 80. The support assembly 30 includes a stud 82 which depends downwardly therefrom and passes through these bearings and

front housing, in addition to a bearing plate 84 held by nut 86 and lock washer 88. The front housing 80 is thus free to pivot with respect to the support assembly 30. That pivotal movement is limited by a stop pin 90 that strikes ends 30a and 30b of a cut-away portion of the plate that constitutes the support assembly 30. The front housing 80 is thus free to pivot about an axis which is coextensive with the stud 82 for at least about 90° of movement about that axis. The axis of the stud 82 is parallel to the axis of pivotal movement of the rear housing 64 described above. Again, the significance of the pivoting movement of the front housing will be described in more detail below.

As shown in Fig. 3, a parallel link mechanism couples together the rear housing 64 and the front housing 80. Specifically, an upper arm 100 and a lower arm 102 constitute the two links of the parallel link mechanism. The upper arm 100 is pivotally coupled by a pivot pin 104 to the rear housing 64. The pivot 104 extends through holes 106 in the upper arm 100 and holes 108 in the rear housing 64, and is held in place by clips 110. Similarly, the lower arm 102 is pivotally coupled to the rear housing 64 by pin 112, which passes through holes 114 in the lower arm and holes 116 in the rear housing. The upper arm 100 is pivotally coupled to the front housing 80 by pin 118, which passes through holes 120 in the front portion of the upper arm 100 and upper holes 122 in the front housing 80. The pin 118 is maintained in place by clip 124. Similarly, the front end of the lower arm 102 is pivotally coupled to the front housing 80 by pin 126 which passes through holes 128 in the front of the lower arm 102 and lower holes 130 in the front housing 80. A gas

OFFICE

cylinder mechanism 132 completes the coupling of rear housing 64 to front housing 80. Specifically, gas cylinder 132 is pivotally connected at one end thereof by pin 134 to a rear portion of the lower arm 102 adjacent to the holes 114. A centering structure 136 is included on both sides of the plates that constitute the sides of the lower arm 102 for the purpose of centering the gas cylinder between those plates. The front end of the gas cylinder 132 (the moveable piston in the gas cylinder) is coupled to a bracket 138. That bracket
10 includes holes 140 therein through which the pin 118 passes. Thus, the moveable piston in the gas cylinder is coupled to the front housing 80 via the pin 118.

The action of the mechanism coupling the rear housing 64 to the front housing 80 is best understood by reference to Fig. 4. The upper arm 100 and lower arm 102 form parallel links. There are two positions of the keyboard mounting plate 10 shown, namely, a high position and a low position. Because of the parallel links 100 and 102, and the pivotal connections provided by the pins 104, 112, 118, and 126, the
20 tilt of the keyboard mounting plate 10 remains constant for all vertical positions of the front housing 80. This action occurs because the upper arm 100 and lower arm 102 form constant radii governing the arcuate movement of the pins 118 and 126 coupled to the front housing 80, pivoting about centers determined by the pins 104 and 112 in the rear housing 64.

Referring now to Figs. 1 and 4 together, the significance of the various axes of pivotal movement of the rear housing 64 and the front housing 80 will now be perceived. The rear housing 64 pivots preferably 360° about the axis 60

OFFICE
LAT

(this is the axis of the same-numbered stud in Fig. 5). Thus the rear housing 64 is free to pivot about an axis which is generally perpendicular to the slide plate 50. When it is desired to store the keyboard mounting plate entirely underneath the work surface, the slide plate 50 may be moved to its rearward-most position, and the rear housing 64 pivoted to the extent necessary to pivot the entire keyboard support plate assembly underneath the work surface. The pivotal movement of the front housing 80, on the other hand, about axis 82 (which is the axis of the stud 82 in Fig. 3) provides for pivotal movement of the front housing about an axis which is parallel to that of the pivotal movement of the rear housing 64. This pivotal movement of the front housing 80 is for the purpose of pivoting the keyboard mounting plate 10 to any desired position in use. Normally, only 90° of a pivoting movement of the front housing is required, and for this reason the stop pin 90 is included, as described above (with respect to Fig. 3). The two angular pivoting movements of the front and rear housings, together with the forward/backward movement of the slide plate 50 provide the necessary movement of the keyboard mounting plate 10 to provide any positioning of that mounting plate desired by a computer operator.

The gas cylinder mechanism participates in the movement of the keyboard mounting plate 10 by providing for the raising and lowering of the front housing 80. With reference to Fig. 6, a gas cylinder activating rod 160 is included that passes through a hole 162 in the bracket 138. The activating rod 160 is fastened to a cam 164 by means of a set screw 166. Movement of the activating rod 160 moves the

30
CHICAGO
LAB

cam 164, which includes a dished surface 164a thereon that bears against activating button 132a of the gas cylinder. Appropriate movement of the activating rod 160 results in actuation of the gas cylinder activating button, in turn permitting the piston in the gas cylinder to move. When the keyboard mounting plate 10 is in the low position shown in Fig. 4, activation of the gas cylinder 132 results in the raising of the mounting plate by outward movement of the piston in the gas cylinder. On the other hand, when it is desired to lower the keyboard mounting plate 10, the gas cylinder is activated by appropriate manipulation of the activating rod 160, and manual force is used to lower the keyboard mounting plate 10 to the desired position.

By use of a gas cylinder mechanism, upward and downward movement of the keyboard mounting plate 10 is easily achieved. A cumbersome spring mechanism normally found in assemblies of this type is avoided by use of the gas cylinder mechanism, and manual force is only required in the lowering of the keyboard mounting plate, upward movement being carried out automatically by the gas cylinder mechanism. The pivotal movement of the front and rear housings in connection with the sliding movement of the slide plate together provide for accurate positioning of the keyboard mounting plate any number of unlited positions and orientations of that mounting plate in front of and below a work surface.

It will be appreciated that modifications of the presently-preferred embodiment described above may be made by those skilled in the art. Accordingly, this invention should be taken to be defined by the appended claims.

Office

The claims defining the invention are as follows:

1. An adjustable keyboard support comprising;

a base;

a pair of spaced generally parallel co-extensive elongated links, each link having an end pivotally attached to said base;

a keyboard mounting plate assembly including a plate to receive and support a keyboard, said plate being pivotally attached to the other ends of said links so that during movement of said plate, the orientation of said plate remains substantially unchanged, said plate assembly further including clamp means to engage said keyboard to retain said keyboard at a position supported on said plate;

a gas cylinder operatively extending between said base and plate assembly to effectively apply a force to aid in maintaining a desired position of said plate.

2. The support of claim 1 wherein said plate assembly includes a front housing upon which said plate is mounted, and said gas cylinder is pivotally attached to said front housing.

3. The support of claim 1 or 2 wherein said gas cylinder is operatively associated with said base, by being pivotally attached to said links adjacent said base.

4. The support of claim 2, or claim 3 when appended to claim 2, further including tilt adjustment means mounting said plate on said front housing enabling tilting of said plate relative to the horizontal.

5. The support of any one of claims 1 to 4, wherein said clamp means includes spaced opposing resilient bumpers which engage the keyboard to retain the keyboard in position.

6. The support of any one of claims 1 to 5, wherein said base includes a rear housing to which said links are pivotally attached, and a mounting member slidably co-operating with said rear housing to permit sliding relative movement therebetween in a direction having a horizontal component.

7. The support of claim 6, wherein said mounting member has a pair of tracks, and said rear housing has a pair of track engaging members, engaged within the tracks to permit the sliding movement between said rear housing and said mounting member.

11.1.14
M
E

8. The support of claim 7, wherein each of said track engaging members includes a bearing means resiliently biased into frictional engagement with the associated track.

9. The support of claim 8, wherein said bearing means are bearing blocks of nylon material.

10. An adjustable keyboard support, substantially as hereinbefore described with reference to the accompanying drawings.

DATED this FOURTEENTH day of OCTOBER 1988
KNOLL INTERNATIONAL, INC.

Patent Attorneys for the Applicant
SPRUSON & FERGUSON






FIG. 2.




FIG. 3.




FIG. 4.




FIG. 6.

